

Praxair Material Safety Data Sheet

1. Chemical Product and Company Identification

Product Name: Nitrous oxide, refrigerated liquid (MSDS No. P-6226-A)	Trade Name: Medipure™ Liquid Nitrous Oxide
Chemical Name: Nitrous Oxide	Synonyms: Nitrous oxide (cryogenic liquid)
Formula: N ₂ O	Chemical Family: Oxide
Telephone:	Company Name: Praxair, Inc. 39 Old Ridgebury Road Danbury, CT 06810-5113
Emergencies: 1-800-645-4633*	
CHEMTREC: 1-800-424-9300*	
Routine: 1-800-PRAXAIR	

* Call emergency numbers 24 hours a day only for spills, leaks, fire, exposure, or accidents involving this product. For routine information, contact your supplier, Praxair sales representative, or call 1-800-PRAXAIR (1-800-772-9247).

2. Composition/Information on Ingredients

See section 16 for important information about mixtures.

INGREDIENT	CAS NUMBER	CONCENTRATION	OSHA PEL	ACGIH TLV-TWA (2004)
Nitrous Oxide	10024-97-2	>99%*	None currently established	50 ppm**

* The symbol > means "greater than."

** Praxair has established its own exposure level at 25 ppm.

3. Hazards Identification

EMERGENCY OVERVIEW

WARNING! Cold, oxidizing liquid and gas under pressure.

Vigorously accelerates combustion.

Can cause rapid suffocation.

Can cause anesthetic effects.

May cause nervous system and blood cell damage.

Reproductive hazard.

May cause frostbite.

May cause dizziness and drowsiness.

Self-contained breathing apparatus and protective clothing may be required by rescue workers.

Odor: Slightly sweet

THRESHOLD LIMIT VALUE: TLV-TWA, 50 ppm (ACGIH, 2004). TLV-TWAs should be used as a guide in the control of health hazards and not as fine lines between safe and dangerous concentrations.

EFFECTS OF A SINGLE (ACUTE) OVEREXPOSURE:

INHALATION—May cause excitation, dizziness, drowsiness, poor coordination, and narcosis.

Exposure to concentrations of 50% or greater will produce clinical anesthesia. High concentrations may cause asphyxia and death from lack of oxygen.

SKIN CONTACT—No harm expected from gas. Liquid may cause frostbite.

SWALLOWING—An unlikely route of exposure. This product is a gas at normal temperature and pressure, but frostbite of the lips and mouth may result from contact with the liquid.

EYE CONTACT—No harm expected from gas. Liquid may cause frostbite.

EFFECTS OF REPEATED (CHRONIC) OVEREXPOSURE: Metabolic injury to the nervous system has resulted from frequent exposure to anesthetic concentrations of nitrous oxide. Complaints include numbness, tingling of hands and legs, loss of feeling in fingers, poor balance, and muscular weakness.

OTHER EFFECTS OF OVEREXPOSURE: Nitrous oxide is an asphyxiant. Lack of oxygen can kill.

MEDICAL CONDITIONS AGGRAVATED BY OVEREXPOSURE: Pregnant women should avoid exposure to nitrous oxide. (See “Significant Laboratory Data” below for further information.)

SIGNIFICANT LABORATORY DATA WITH POSSIBLE RELEVANCE TO HUMAN HEALTH

HAZARD EVALUATION: Exposure to nitrous oxide has produced embryofetal toxicity in laboratory animals as evidenced by reduced fetal weight, delayed ossification, and increased incidence of visceral and skeletal variations. Exposure to nitrous oxide may be associated with an increased incidence of abortion in humans. Single prolonged exposure to high concentrations of nitrous oxide has resulted in bone marrow injury and adverse effects on the blood.

CARCINOGENICITY: Nitrous oxide is not listed by NTP, OSHA, or IARC.

4. First Aid Measures

INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, qualified personnel may give oxygen. Call a physician.

SKIN CONTACT: For exposure to liquid, immediately warm frostbite area with warm water not to exceed 105°F (41°C). In case of massive exposure, remove contaminated clothing while showering with warm water. Call a physician.

SWALLOWING: An unlikely route of exposure. This product is a gas at normal temperature and pressure.

EYE CONTACT: For exposure to liquid, immediately flush eyes thoroughly with warm water for at least 15 minutes. Hold the eyelids open and away from the eyeballs to ensure that all surfaces are flushed thoroughly. See a physician, preferably an ophthalmologist, immediately.

NOTES TO PHYSICIAN: *Nitrous oxide may cause vitamin B-12 deficiency. This chemically induced deficiency may result in megaloblastic anemia and damage to the nervous system. When administered for anesthetic purposes, nitrous oxide may suppress immunological function, reducing resistance to infection and to other immuno-dependent disease processes.*

5. Fire Fighting Measures

FLASH POINT (test method):	Not applicable	
AUTOIGNITION TEMPERATURE:	Not applicable	
FLAMMABLE LIMITS IN AIR , % by volume:	LOWER: Not applicable	UPPER: Not applicable
EXTINGUISHING MEDIA: This product cannot catch fire. Use media appropriate for surrounding fire.		

SPECIAL FIRE FIGHTING PROCEDURES: WARNING! Cold, oxidizing liquid and gas under pressure. Evacuate all personnel from danger area. Immediately spray containers with water from maximum distance until cool, taking care not to direct spray onto vents on top of container. Do not discharge sprays into liquid product. Liquid nitrous oxide will freeze water rapidly. When containers have cooled, move them away from fire area if without risk. Self-contained breathing apparatus may be required by rescue workers. On-site fire brigades must comply with OSHA 29 CFR 1910.156.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Oxidizing agent; may accelerate combustion. Vapors form from this product and may travel or be moved by air currents to locations distant from the product handling point. Contact with combustible materials such as oil, grease, and other hydrocarbon products, especially in the presence of ignition sources such as pilot lights, other flames, smoking, sparks, heaters, electrical equipment, and static discharges may cause fire or explosion. Heat of fire can build pressure in closed container and cause it to rupture. No part of a container should be subjected to a temperature higher than 125°F (52°C). Liquid nitrous oxide containers are equipped with pressure relief devices. Venting vapors may obscure visibility. Liquid causes severe frostbite, a burn-like injury. (See section 3.)

HAZARDOUS COMBUSTION PRODUCTS: Not applicable

6. Accidental Release Measures

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: WARNING! Cold, oxidizing liquid and gas under pressure. Immediately evacuate all personnel from danger area. Use self-contained breathing apparatus where needed. Nitrous oxide is an asphyxiant. Lack of oxygen can kill. Vapors can spread from spill. Contact with flammable materials may cause fire or explosion. (See section 5.) Test for sufficient oxygen, especially in confined areas, before allowing reentry. Use self-contained breathing apparatus where needed. Shut off leak if without risk. Ventilate area of leak or move container to a well-ventilated area.

WASTE DISPOSAL METHOD: Prevent waste from contaminating the surrounding environment. Keep personnel away. Discard any product, residue, disposable container, or liner in an environmentally acceptable manner, in full compliance with federal, state, and local regulations. If necessary, call your local supplier for assistance.

7. Handling and Storage

PRECAUTIONS TO BE TAKEN IN STORAGE: Store and use with adequate ventilation, away from oil, grease, and other hydrocarbons. Do not store in a confined space. Cryogenic containers are equipped with a pressure relief device and a pressure controlling valve. Under normal conditions, these containers will periodically vent product. Separate nitrous oxide containers from flammables by at least 20 ft (6.1 m) or use a barricade of noncombustible material. This barricade should be at least 5 ft (1.53 m) high and

have a fire resistance rating of at least ½ hour. Store only where temperature will not exceed 125°F (52°C).

PRECAUTIONS TO BE TAKEN IN HANDLING: Protect containers from damage. Use a suitable hand truck to move containers. Cryogenic containers must be handled and stored in an upright position. Do not drop or tip containers, or roll them on their sides. If valve is hard to open, discontinue use and contact your supplier. For other precautions in using nitrous oxide, see section 16.

For further information on storage, handling, and use of this product, see NFPA 55, *Standard for the Storage, Use, and Handling of Compressed and Liquefied Gases in Portable Cylinders*, published by the National Fire Protection Association.

8. Exposure Controls/Personal Protection

VENTILATION/ENGINEERING CONTROLS:

LOCAL EXHAUST—Use a local exhaust system, if necessary, to control the concentration of nitrous oxide in the worker's breathing zone.

MECHANICAL (general)—Not recommended as a primary ventilation system to control worker's exposure.

SPECIAL—None

OTHER—None

RESPIRATORY PROTECTION: Use an air-supplied respirator or a full-face, positive-pressure, self-contained breathing apparatus. Respiratory protection must conform to OSHA 29 CFR 1910.134. Select per OSHA 29 CFR 1910.134 and ANSI Z88.2.

SKIN PROTECTION: Wear loose-fitting cryogenic gloves. Gloves must be free of oil and grease.

EYE PROTECTION: Wear safety glasses and a full face shield. Select in accordance with OSHA 29 CFR 1910.133.

OTHER PROTECTIVE EQUIPMENT: Metatarsal shoes for container handling; protective clothing where needed. Cuffless trousers should be worn outside the shoes. Select in accordance with OSHA 29 CFR 1910.132 and 1910.133. Regardless of protective equipment, never touch live electrical parts.

9. Physical and Chemical Properties

MOLECULAR WEIGHT:	44.0128
SPECIFIC GRAVITY (H ₂ O = 1) at -127/60°F (-88.3/15.6°C):	1.23
SPECIFIC GRAVITY (Air = 1) at 70°F (21.1°C) and 1 atm:	1.5297
EXPANSION RATIO for liquid at boiling point to gas at 70°F (21.1°C):	Approx. 1 to 670
SOLUBILITY IN WATER , vol/vol at 68°F (20°C) and 1 atm:	0.68
PERCENT VOLATILES BY VOLUME:	100
BOILING POINT at 1 atm:	-127.26°F (-88.48°C)
MELTING POINT at 1 atm:	-131.48°F (-90.82°C)

APPEARANCE, ODOR, AND STATE: Colorless cryogenic liquid; vapor has slightly sweet odor and taste.

10. Stability and Reactivity

STABILITY: Unstable Stable

INCOMPATIBILITY (materials to avoid): Flammable materials, hydrocarbons such as oils and grease, asphalt, ethers, alcohols, acids, and aldehydes. Alkali metals, boron, tungsten carbide, and powdered aluminum.

HAZARDOUS DECOMPOSITION PRODUCTS: Excess heat. Nitrous oxide decomposes explosively at 1,202°F (650°C) into two parts nitrogen to one part oxygen. In the presence of catalytic surfaces such as silver, platinum, cobalt, and copper or nickel oxides, this reaction occurs at lower temperatures.

HAZARDOUS POLYMERIZATION: May Occur Will Not Occur

CONDITIONS TO AVOID: None known.

11. Toxicological Information

See section 3.

12. Ecological Information

No adverse ecological effects expected. Nitrous oxide does not contain any Class I or Class II ozone-depleting chemicals. Nitrous oxide is not listed as a marine pollutant by DOT.

13. Disposal Considerations

WASTE DISPOSAL METHOD: Do not attempt to dispose of residual or unused quantities. Return container to supplier.

14. Transport Information

DOT/IMO SHIPPING NAME: Nitrous oxide, refrigerated liquid

HAZARD CLASS:	IDENTIFICATION NUMBER:	PRODUCT RQ:
2.2	UN 2201	None
SHIPPING LABEL(s): NONFLAMMABLE GAS, OXIDIZER		
PLACARD (when required): NONFLAMMABLE GAS, OXIDIZER		

SPECIAL SHIPPING INFORMATION: Cylinders should be transported in a secure position, in a well-ventilated vehicle. Cylinders transported in an enclosed, nonventilated compartment of a vehicle can present serious safety hazards.

Shipment of compressed gas cylinders that have been filled without the owner's consent is a violation of federal law [49 CFR 173.301(b)].

15. Regulatory Information

The following selected regulatory requirements may apply to this product. Not all such requirements are identified. Users of this product are solely responsible for compliance with all applicable federal, state, and local regulations.

U.S. FEDERAL REGULATIONS:**EPA (ENVIRONMENTAL PROTECTION AGENCY)**

CERCLA: COMPREHENSIVE ENVIRONMENTAL RESPONSE, COMPENSATION, AND LIABILITY ACT OF 1980 (40 CFR Parts 117 and 302):

Reportable Quantity (RQ): None

SARA: SUPERFUND AMENDMENT AND REAUTHORIZATION ACT:

SECTIONS 302/304: Require emergency planning based on Threshold Planning Quantity (TPQ) and release reporting based on Reportable Quantities (RQ) of Extremely Hazardous Substances (EHS) (40 CFR Part 355):

TPQ: None

EHS RQ: None

SECTIONS 311/312: Require submission of MSDSs and reporting of chemical inventories with identification of EPA hazard categories. The hazard categories for this product are as follows:

IMMEDIATE: Yes

PRESSURE: Yes

DELAYED: Yes

REACTIVITY: No

FIRE: Yes

SECTION 313: Requires submission of annual reports of release of toxic chemicals that appear in 40 CFR Part 372.

Nitrous oxide does not require reporting under Section 313.

40 CFR 68: RISK MANAGEMENT PROGRAM FOR CHEMICAL ACCIDENTAL RELEASE PREVENTION: Requires development and implementation of risk management programs at facilities that manufacture, use, store, or otherwise handle regulated substances in quantities that exceed specified thresholds.

Nitrous oxide is not listed as a regulated substance.

TSCA: TOXIC SUBSTANCES CONTROL ACT: Nitrous oxide is listed on the TSCA inventory.

OSHA: OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION:

29 CFR 1910.119: PROCESS SAFETY MANAGEMENT OF HIGHLY HAZARDOUS CHEMICALS: Requires facilities to develop a process safety management program based on Threshold Quantities (TQ) of highly hazardous chemicals.

Nitrous oxide is not listed in Appendix A as a highly hazardous chemical.

STATE REGULATIONS:

CALIFORNIA: Nitrous oxide is not listed by California under the SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT OF 1986 (Proposition 65).

PENNSYLVANIA: Nitrous oxide is subject to the PENNSYLVANIA WORKER AND COMMUNITY RIGHT-TO-KNOW ACT (35 P.S. Sections 7301-7320).

16. Other Information

Be sure to read and understand all labels and instructions supplied with all containers of this product.

OTHER HAZARDOUS CONDITIONS OF HANDLING, STORAGE, AND USE: *Cold, oxidizing liquid and gas under pressure.* Clean all gauges, valves, regulators, piping, and equipment as for oxygen

service in accordance with CGA pamphlet G-4.1. Never substitute CO₂ equipment for N₂O equipment unless the CO₂ equipment has been disassembled and cleaned for oxygen service. Keep containers and their valves free of oil and grease. **Use piping and equipment adequately designed to withstand pressures to be encountered.** Avoid materials incompatible with cryogenic use; some metals such as carbon steel may fracture easily at low temperature. **Prevent reverse flow.** Reverse flow into container may cause rupture. Use a check valve or other protective device in any line or piping from the container. **Gas can cause rapid suffocation due to oxygen deficiency.** Store and use with adequate ventilation. Close cylinder valve after each use; keep closed even when empty. **Never work on a pressurized system.** If there is a leak, close the cylinder valve. Blow the system down in a safe and environmentally sound manner in compliance with all federal, state, and local laws; then repair the leak. **Never place a compressed gas cylinder where it may become part of an electrical circuit.**

Recommended Equipment: In semiconductor process gas and other suitable applications, Praxair recommends the use of engineering controls such as gas cabinet enclosures, automatic gas panels (used to purge systems on cylinder changeout), excess-flow valves throughout the gas distribution system, double containment for the distribution system, and continuous gas monitors.

MIXTURES: When you mix two or more gases or liquefied gases, you can create additional, unexpected hazards. Obtain and evaluate the safety information for each component before you produce the mixture. Consult an industrial hygienist or other trained person when you evaluate the end product. Remember, gases and liquids have properties that can cause serious injury or death.

HAZARD RATING SYSTEMS:

NFPA RATINGS:

HEALTH	= 3
FLAMMABILITY	= 0
INSTABILITY	= 0
SPECIAL	= OX

HMIS RATINGS:

HEALTH	= 3
FLAMMABILITY	= 0
PHYSICAL HAZARD	= 2

STANDARD VALVE CONNECTIONS FOR U.S. AND CANADA:

THREADED:

CGA-326 Gas Withdrawal
CGA-624 Refrigerated Liquid Withdrawal

PIN-INDEXED YOKE:

Not applicable

ULTRA-HIGH-INTEGRITY CONNECTION:

CGA-712, but not generally applicable for Liquid Containers

Use the proper CGA connections. **DO NOT USE ADAPTERS.** Additional limited-standard connections may apply. See CGA pamphlet V-1 listed below.

Ask your supplier about free Praxair safety literature as referred to in this MSDS and on the label for this product. Further information about this product can be found in the following pamphlets published by the Compressed Gas Association, Inc. (CGA), 4221 Walney Road, 5th Floor, Chantilly, VA 20151-2923, Telephone (703) 788-2700, <http://www.cganet.com/Publication.asp>.

- AV-1 *Safe Handling and Storage of Compressed Gases*
- AV-8 *Characteristics and Safe Handling of Cryogenic Liquid and Gaseous Oxygen*
- G-4.1 *Cleaning Equipment for Oxygen Service*
- G-8.1 *Standard for Nitrous Oxide Systems at Consumer Sites*
- P-1 *Safe Handling of Compressed Gases in Containers*
- SB-2 *Oxygen-Deficient Atmospheres*
- SB-6 *Nitrous Oxide Security and Control*
- V-1 *Compressed Gas Cylinder Valve Inlet and Outlet Connections*
- *Handbook of Compressed Gases, Fourth Edition*

Praxair asks users of this product to study this MSDS and become aware of product hazards and safety information. To promote safe use of this product, a user should (1) notify employees, agents, and contractors of the information in this MSDS and of any other known product hazards and safety information, (2) furnish this information to each purchaser of the product, and (3) ask each purchaser to notify its employees and customers of the product hazards and safety information.

The opinions expressed herein are those of qualified experts within Praxair, Inc. We believe that the information contained herein is current as of the date of this Material Safety Data Sheet. Since the use of this information and the conditions of use of the product are not within the control of Praxair, Inc., it is the user's obligation to determine the conditions of safe use of the product.

Praxair MSDSs are furnished on sale or delivery by Praxair or the independent distributors and suppliers who package and sell our products. To obtain current Praxair MSDSs for these products, contact your Praxair sales representative or local distributor or supplier, or download from www.praxair.com. If you have questions regarding Praxair MSDSs, would like the form number and date of the latest MSDS, or would like the names of the Praxair suppliers in your area, phone or write the Praxair Call Center (**Phone:** 1-800-PRAXAIR; **Address:** Praxair Call Center, Praxair, Inc., PO Box 44, Tonawanda, NY 14151-0044).

Praxair, the *Flowing Airstream* design, and *Medipure* are trademarks or registered trademarks of Praxair Technology, Inc. in the United States and other countries.



Praxair, Inc.
39 Old Ridgebury Road
Danbury, CT 06810-5113