Page 1 of 10

Praxair Material Safety Data Sheet

1. Chemical Product and Company Identification				
Product Name: Oxygen, refrigerated liquid (MSDS No. P-4637-G) Trade Name: Liquid Oxygen, Medipure [™] Liquid Oxygen				
Chemical Name: Oxygen		Synonyms: Oxygen (cryogenic liquid)		
Formula: O ₂		Chemical Family: Cryogenic liquid		
Telephone:	Emergencies: CHEMTREC: Routine:	1-800-645-4633* 1-800-424-9300* 1-800-PRAXAIR	Company Name:	Praxair, Inc. 39 Old Ridgebury Road Danbury, CT 06810-5113

* Call emergency numbers 24 hours a day only for spills, leaks, fire, exposure, or accidents involving this product. For routine information, contact your supplier, Praxair sales representative, or call 1-800-PRAXAIR (1-800-772-9247).

2. Composition/Information on Ingredients

See section 16 for important information about mixtures.				
		CONCEN- TRATION	OSHA PEL	ACGIH TLV-TWA (2004)
Oxygen	7782-44-7	>99%*	None currently established	None currently establishe

*The symbol > means "greater than."

3. Hazards Identification

EMERGENCY OVERVIEW

WARNING! Extremely cold, oxidizing liquid and gas under pressure. Vigorously accelerates combustion. Combustibles in contact with liquid oxygen may explode on ignition or impact. Can cause severe frostbite. May cause dizziness and drowsiness. Self-contained breathing apparatus and protective clothing may be required by rescue workers. Odor: None

THRESHOLD LIMIT VALUE: None currently established (ACGIH, 2004).

EFFECTS OF A SINGLE (ACUTE) OVEREXPOSURE:

INHALATION–Breathing 80% or more oxygen at atmospheric pressure for more than a few hours may cause nasal stuffiness, cough, sore throat, chest pain, and breathing difficulty. At higher pressures, adverse effects from breathing pure oxygen are more likely and may occur sooner. Breathing pure oxygen under pressure may damage the lungs and affect the Central Nervous System (CNS), producing dizziness, poor coordination, a tingling sensation, visual and hearing disturbances,

Copyright © 1979, 1981, 1985, 1992, 1997, 2003-2004, Praxair Technology, Inc. All rights reserved.

Revised

muscular twitching, unconsciousness, and convulsions. Persons who breathe oxygen under pressure may adapt more slowly to darkness and may suffer reduced peripheral vision.

SKIN CONTACT-No harm expected from vapor. Cold gas or liquid may cause severe frostbite.

SWALLOWING–An unlikely route of exposure, but severe frostbite of the lips and mouth may result from contact with the liquid.

EYE CONTACT-No harm expected from vapor. Cold gas or liquid may cause severe frostbite.

EFFECTS OF REPEATED (CHRONIC) OVEREXPOSURE: No harm expected.

OTHER EFFECTS OF OVEREXPOSURE: See section 11, Toxicological Information.

MEDICAL CONDITIONS AGGRAVATED BY OVEREXPOSURE: See section 11, Toxicological Information.

SIGNIFICANT LABORATORY DATA WITH POSSIBLE RELEVANCE TO HUMAN HEALTH HAZARD EVALUATION: None known.

CARCINOGENICITY: Oxygen is not listed by NTP, OSHA, or IARC.

4. First Aid Measures

INHALATION: Immediately remove to fresh air. If not breathing, give artificial respiration. Keep victim warm and at rest. Call a physician. Advise the physician that the victim has been exposed to a high concentration of oxygen.

SKIN CONTACT: For exposure to liquid, immediately warm frostbite area with warm water not to exceed 105°F (41°C). In case of massive exposure, remove clothing while showering with warm water. Call a physician.

SWALLOWING: An unlikely route of exposure. This product is a gas at normal temperature and pressure.

EYE CONTACT: Immediately flush eyes thoroughly with warm water for at least 15 minutes. Hold the eyelids open and away from the eyeballs to ensure that all surfaces are flushed thoroughly. See a physician, preferably an ophthalmologist, immediately.

NOTES TO PHYSICIAN: Supportive treatment should include immediate sedation, anti-convulsive therapy if needed, and rest. See section 11, Toxicological Information.

5. Fire Fighting Measures			
FLASH POINT (test method): Not applicable			
AUTOIGNITION TEMPERATURE:	Not applicable		
FLAMMABLE LIMITS IN AIR, % by volume:	LOWER: Not applicable UPPER: Not applicable		

EXTINGUISHING MEDIA: Vigorously accelerates combustion. Use media appropriate for surrounding fire. Water (e.g., safety shower) is the preferred extinguishing media for clothing fires.

SPECIAL FIRE FIGHTING PROCEDURES: WARNING! Extremely cold, oxidizing liquid and gas under pressure. Evacuate all personnel from danger area. Immediately spray containers with water from maximum distance until cool, taking care not to direct spray onto vents on top of container. Do not discharge sprays into liquid oxygen. Liquid oxygen will freeze water rapidly. When containers have cooled, move them away from fire area if without risk. Self-contained breathing apparatus may be required by rescue workers. On-site fire brigades must comply with OSHA 29 CFR 1910.156.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Oxidizing agent; vigorously accelerates combustion. Contact with flammable materials may cause fire or explosion. Do not walk on or roll equipment over spill; any impact could cause an explosion. Smoking, flames, and electric sparks are potential explosion hazards in oxygen-enriched atmospheres. Heat of fire can build pressure in a closed container and cause it to rupture. No part of a container should be subjected to a temperature higher than 125°F (52°C). Liquid oxygen containers are equipped with pressure relief devices. Venting vapors may obscure visibility. Liquid causes severe frostbite, a burn-like injury. (See section 3.)

Air will condense on surfaces such as vaporizers and piping exposed to liquid or cold gas. Nitrogen, which has a lower boiling point than oxygen, will evaporate first, leaving an oxygen-enriched condensate. Keep all areas of possible condensation free of oil, grease, and other combustible materials to prevent possible ignition or explosion.

HAZARDOUS COMBUSTION PRODUCTS: Not applicable.

6. Accidental Release Measures

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: WARNING! Extremely cold, oxidizing liquid and gas under pressure. Immediately evacuate all personnel from danger area. Avoid contact with spilled liquid and allow it to evaporate. Extremely cold oxidizing liquid and gas. Liquid causes severe frostbite, a burn-like injury. (See section 3.) Do not walk on or roll equipment over spill; any impact could cause an explosion. Contact with flammable materials may cause fire or explosion. Smoking, flames, and electric sparks are potential explosion hazards in enriched oxygen atmospheres. Shut off leak if without risk. Ventilate area or move leaking container to ventilated area. Remove all flammable materials from vicinity. Oxygen must never be permitted to strike an oily surface, greasy clothes, or other combustible material.

EMERGENCY DISPOSAL MEASURES: Keep personnel away. Liquid oxygen should be dumped into an outdoor pit filled with clean gravel free of grease and oil, where it will safely evaporate. Prevent waste from contaminating the surrounding environment. Discard any product, residue, disposable container, or liner in an environmentally acceptable manner, in full compliance with federal, state, and local regulations. If necessary, call your local supplier for assistance.

7. Handling and Storage

PRECAUTIONS TO BE TAKEN IN STORAGE: Store and use with adequate ventilation, away from oil, grease, and other hydrocarbons. Store only where temperature will not exceed 125°F (52°C). Do not store in a confined space. Cryogenic containers are equipped with a pressure relief device and a pressure controlling valve. Under normal conditions, these containers will periodically vent product. Separate oxygen containers from flammables by at least 20 ft (6.1 m) or use a barricade of noncombustible material. This barricade should be at least 5 ft (1.53 m) and have a fire resistance rating of at least ½ hour. Use adequate pressure relief devices in systems and piping to prevent pressure buildup; entrapped liquid can generate extremely high pressures when vaporized by warming.

PRECAUTIONS TO BE TAKEN IN HANDLING: Never allow any unprotected part of your body to touch uninsulated pipes or vessels containing cryogenic fluids. Flesh will stick to the extremely cold metal and will tear when you try to pull free. Use a suitable hand truck to move containers. Cryogenic containers must be handled and stored in an upright position. Do not drop or tip containers, or roll them on their sides. If valve is hard to open, discontinue use and contact your supplier. For other precautions in using oxygen, see section 16.

For further information on storage, handling, and use of this product, see NFPA 55, *Standard for the Storage, Use, and Handling of Compressed and Liquefied Gases in Portable Cylinders*, published by the National Fire Protection Association.

8. Exposure Controls/Personal Protection

VENTILATION/ENGINEERING CONTROLS:

LOCAL EXHAUST–Use a local exhaust system, if necessary, to prevent increased oxygen concentration.

MECHANICAL (general)-Adequate

SPECIAL–None

OTHER–None

RESPIRATORY PROTECTION: None required under normal use. However, an air-supplied respirator must be used while working in confined spaces with this product. The respiratory protection used must conform with OSHA rules as specified in 29 CFR 1910.134. Select per OSHA 29 CFR 1910.134 and ANSI Z88.2.

SKIN PROTECTION: Wear loose-fitting, cryogenic gloves. Gloves must be free of oil and grease.

EYE PROTECTION: Safety glasses and a full face shield are recommended. Select in accordance with OSHA 29 CFR 1910.133.

OTHER PROTECTIVE EQUIPMENT: Metatarsal shoes for container handling. Protective clothing where needed. Cuffless trousers should be worn outside the shoes. Select in accordance with OSHA 29 CFR 1910.132 and 1910.133. Regardless of protective equipment, never touch live electrical parts.

9. Physical and Chemical Properties			
MOLECULAR WEIGHT:	31.9988		
EXPANSION RATIO:	1 to 860.5		
SPECIFIC GRAVITY ($H_2O = 1$) at boiling point:	1.141		
SPECIFIC GRAVITY (Air = 1) at 70°F (21.1°C) and 1 atm:	1.105		
PERCENT VOLATILES BY VOLUME:	100		
EVAPORATION RATE (Butyl Acetate = 1):	High		
BOILING POINT at 1 atm:	-297.4°F (-183°C)		
FREEZING POINT at 1 atm:	-361.1°F (-218.4°C)		

APPEARANCE, ODOR, AND STATE: Pale blue, odorless cryogenic liquid

10. Stability and Reactivity				
STABILITY:	Unstable	⊠ Stable		
INCOMPATIBILITY (materials to avoid): Flammable materials, hydrocarbons such as oils and grease, asphalt, ethers, alcohols, acids, and aldehydes. Oxygen reacts with many materials.				
HAZARDOUS DECOMPOSITION PRODUCTS: None known.				
HAZARDOUS POLYMERIZATION: May Occur Will Not Occur				
CONDITIONS TO AVOID: None known.				

11. Toxicological Information

At atmospheric concentration and pressure, oxygen poses no toxicity hazards. At high concentrations, newborn premature infants may suffer delayed retinal damage (retrolental fibroplasia) that can progress to retinal detachment and blindness. Retinal damage may also occur in adults exposed to 100% oxygen for extended periods (24 to 48 hours) or at pressures exceeding atmospheric pressure, particularly in individuals whose retinal circulation has been previously compromised. All individuals exposed for long periods to oxygen at high pressure and all who exhibit overt oxygen toxicity should have ophthalmologic examinations.

At two or more atmospheres, toxicity to the CNS occurs. Symptoms include nausea, vomiting, dizziness or vertigo, muscle twitching, vision changes, and loss of consciousness and generalized seizures. At three atmospheres, CNS toxicity occurs in less than two hours; at six atmospheres, in only a few minutes.

Patients with chronic obstructive pulmonary disease retain carbon dioxide abnormally. If oxygen is administered, raising their blood-oxygen concentration, their breathing becomes depressed, and retained carbon dioxide rises to a dangerous level.

Animal studies suggest that the administration of certain drugs, including phenothiazine drugs and chloroquine, increases the susceptibility to toxicity from oxygen at high concentrations or pressures. Animal studies also indicate that vitamin E deficiency may increase susceptibility to oxygen toxicity.

Airway obstruction during high oxygen tension may cause alveolar collapse following absorption of the oxygen. Similarly, occlusion of the eustachian tubes may cause retraction of the eardrum and obstruction of the paranasal sinuses may produce vacuum-type headache.

12. Ecological Information

The atmosphere contains approximately 21% oxygen. No adverse ecological effects expected. Oxygen does not contain any Class I or Class II ozone-depleting chemicals. Oxygen is not listed as a marine pollutant by DOT.

13. Disposal Considerations

WASTE DISPOSAL METHOD: Do not attempt to dispose of residual or unused quantities. Contact your supplier. For emergency disposal, discharge slowly to the atmosphere in a well-ventilated area or outdoors. Also see section 6 for disposal following spills.

14. Transport Information				
DOT/IMO SHIPPING NAME:	Oxygen, refrigerated liquid			
HAZARD CLASS: 2.2 IDENTIFICATION NUMBER: UN 1073 PRODUCT RQ: Non				None
SHIPPING LABEL(s):	OXYGEN. An oxygen label may be used for domestic shipment in the United States and Canada in place of the NONFLAMMABLE GAS and OXIDIZER labels (49 CFR Part 172).		the United	
PLACARD (when required):	· ·			

SPECIAL SHIPPING INFORMATION: Containers should be transported in a secure position, in a well-ventilated vehicle. Containers transported in an enclosed, nonventilated compartment of a vehicle can present serious safety hazards.

Shipment of compressed gas cylinders that have been filled without the owner's consent is a violation of federal law [49 CFR 173.301(b)].

15. Regulatory Information

The following selected regulatory requirements may apply to this product. Not all such requirements are identified. Users of this product are solely responsible for compliance with all applicable federal, state, and local regulations.

U.S. FEDERAL REGULATIONS:

EPA (ENVIRONMENTAL PROTECTION AGENCY)

CERCLA: COMPREHENSIVE ENVIRONMENTAL RESPONSE, COMPENSATION, AND LIABILITY ACT OF 1980 (40 CFR Parts 117 and 302):

Reportable Quantity (RQ): None

SARA: SUPERFUND AMENDMENT AND REAUTHORIZATION ACT:

SECTIONS 302/304: Require emergency planning based on Threshold Planning Quantity (TPQ) and release reporting based on Reportable Quantities (RQ) of Extremely Hazardous Substances (EHS) (40 CFR Part 355):

TPQ: None EHS RQ: None

SECTIONS 311/312: Require submission of MSDSs and reporting of chemical inventories with identification of EPA hazard categories. The hazard categories for this product are as follows:

IMMEDIATE: Yes	PRESSURE: Yes
DELAYED: No	REACTIVITY: No
	FIRE: Yes

SECTION 313: Requires submission of annual reports of release of toxic chemicals that appear in 40 CFR Part 372.

Oxygen does not require reporting under Section 313.

40 CFR 68: RISK MANAGEMENT PROGRAM FOR CHEMICAL ACCIDENTAL RELEASE PREVENTION: Requires development and implementation of risk management programs at facilities that manufacture, use, store, or otherwise handle regulated substances in quantities that exceed specified thresholds.

Oxygen is not listed as a regulated substance.

TSCA: TOXIC SUBSTANCES CONTROL ACT: Oxygen is listed on the TSCA inventory. **OSHA:** OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION:

29 CFR 1910.119: PROCESS SAFETY MANAGEMENT OF HIGHLY HAZARDOUS CHEMICALS: Requires facilities to develop a process safety management program based on Threshold Quantities (TQ) of highly hazardous chemicals.

Oxygen is not listed in Appendix A as a highly hazardous chemical.

STATE REGULATIONS:

CALIFORNIA: This product is not listed by California under the SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT OF 1986 (Proposition 65).

PENNSYLVANIA: This product is subject to the PENNSYLVANIA WORKER AND COMMUNITY RIGHT-TO-KNOW ACT (35 P.S. Sections 7301-7320).

16. Other Information

Be sure to read and understand all labels and instructions supplied with all containers of this product.

WARNING: Medical grades of oxygen are subject to strict federal regulation and are for use only under the control of a licensed physician or clinician familiar with the product and its hazards.

SPECIAL PRECAUTIONS: *Extremely cold, oxidizing liquid and gas under pressure.* All gauges, valves, regulators, piping, and equipment to be used in oxygen service must be cleaned for oxygen service in accordance with CGA pamphlet G-4.1. Keep containers and their valves free of oil and grease. Use piping and equipment adequately designed to withstand the pressures to be encountered. Avoid materials incompatible with cryogenic use; some metals such as carbon steel may fracture easily at low temperature. To prevent cryogenic liquid or cold gas from being trapped in piping between valves, equip the piping with pressure relief devices; entrapped liquid can generate extremely high pressures when vaporized by warming. Use only transfer lines designed for cryogenic liquids. Praxair recommends piping all vents to the exterior of the building. Never use oxygen as a substitute for compressed air. Never use an oxygen jet for cleaning of any sort, especially for cleaning clothing. Oxygen-saturated clothing may burst into flame at the slightest spark and be quickly consumed in an engulfing fire. Do not get liquid in eyes, on skin, or on clothing. Persons exposed to liquid high concentrations of oxygen gas should stay in a well-ventilated or open area for 30 minutes before entering a confined space or going near any source of ignition. *Never work on a pressurized system.* If a leak occurs, close the cylinder valve. Blow the system down in a safe and environmentally sound manner in compliance with all federal, state, and local laws; then repair the leak. Never place a compressed gas cylinder where it may become part of an electrical circuit.

OTHER HAZARDOUS CONDITIONS OF HANDLING, STORAGE, AND USE: Store and use with adequate ventilation. Close valve after each use; keep closed even when empty. Immediately remove clothing exposed to oxygen and air it out to reduce the likelihood of an engulfing fire. Prevent ignition sources such as static electricity generated in clothing while walking. Protect container against physical damage. Isolate it from combustible gas installations and combustible materials by an adequate distance or by gas-tight, fire resistant barriers. Protect against overheating.

Use of this product in manufacturing may generate toxic fumes and gases or create additional toxicity hazards. Consult an industrial hygienist or other appropriately trained person to evaluate end-use operations or processes for hazards and to establish measures to protect employees.

MIXTURES: When you mix two or more gases or liquefied gases, you can create additional, unexpected hazards. Obtain and evaluate the safety information for each component before you produce the mixture. Consult an industrial hygienist or other trained person when you evaluate the end product. Remember, gases and liquids have properties that can cause serious injury or death.

HAZARD RATING SYSTEMS:

NFPA RATINGS:	H	MIS RATINGS:	
HEALTH	= 3	HEALTH	= 3
FLAMMABILITY	= 0	FLAMMABILITY	= 0
INSTABILITY	= 0	PHYSICAL HAZARD	= 2
SPECIAL	= OX (OXidizer)		

STANDARD VALVE CONNECTIONS FOR U.S. AND CANADA:

THREADED:	CGA-440 (cryogenic liquid withdrawal)
PIN-INDEXED YOKE:	Not applicable
ULTRA-HIGH-INTEGRITY CONNECTION:	Not applicable

Use the proper CGA connections. **DO NOT USE ADAPTERS.** Additional limited-standard connections may apply. See CGA pamphlets V-1 and V-7 listed below.

Ask your supplier about free Praxair safety literature as referred to in this MSDS and on the label for this product. Further information about this product can be found in the following pamphlets published by the Compressed Gas Association, Inc. (CGA), 4221 Walney Road, 5th Floor, Chantilly, VA 20151-2923, Telephone (703) 788-2700, http://www.cganet.com/Publication.asp.

- AV-1 Safe Handling and Storage of Compressed Gases
- AV-8 Characteristics and Safe Handling of Cryogenic Liquid and Gaseous Oxygen
- G-4 Oxygen
- G-4.1 *Cleaning Equipment for Oxygen Service*
- P-1 Safe Handling of Compressed Gases in Containers
- P-2 Characteristics and Safe Handling of Medical Gases
- P-12 Safe Handling of Cryogenic Liquids
- P-39 Oxygen-Rich Atmospheres
- SB-2 Oxygen-Deficient Atmospheres
- SB-8 Use of Oxy-Fuel Gas Welding and Cutting Apparatus
- V-1 Compressed Gas Cylinder Valve Inlet and Outlet Connections
- Handbook of Compressed Gases, Fourth Edition

Praxair asks users of this product to study this MSDS and become aware of product hazards and safety information. To promote safe use of this product, a user should (1) notify employees, agents, and contractors of the information in this MSDS and of any other known product hazards and safety information, (2) furnish this information to each purchaser of the product, and (3) ask each purchaser to notify its employees and customers of the product hazards and safety information.

The opinions expressed herein are those of qualified experts within Praxair, Inc. We believe that the information contained herein is current as of the date of this Material Safety Data Sheet. Since the use of this information and the conditions of use of the product are not within the control of Praxair, Inc., it is the user's obligation to determine the conditions of safe use of the product.

Praxair MSDSs are furnished on sale or delivery by Praxair or the independent distributors and suppliers who package and sell our products. To obtain current Praxair MSDSs for these products, contact your Praxair sales representative or local distributor or supplier, or download from www.praxair.com. If you have questions regarding Praxair MSDSs, would like the form number and date of the latest MSDS, or would like the names of the Praxair suppliers in your area, phone or write the Praxair Call Center (**Phone:** 1-800-PRAXAIR; **Address:** Praxair Call Center, Praxair, Inc., PO Box 44, Tonawanda, NY 14151-0044).

Praxair, the *Flowing Airstream* design, and *Medipure* are trademarks or registered trademarks of Praxair Technology, Inc. in the United States and other countries.



Praxair, Inc. 39 Old Ridgebury Road Danbury, CT 06810-5113