





Tiger® Surface Conditioning Discs & Back-up Pads / Wire Wheels

Surface Conditioning Discs







Hook & Style D		(
Dia.	Grade	Part No.
2"	Very Fine (Blue) Medium (Maroon) Coarse (Brown)	51503 51504 51505
3"	Very Fine (Blue) Medium (Maroon) Coarse (Brown)	51506 51507 51508
4"	Very Fine (Blue) Medium (Maroon) Coarse (Brown)	51509 51510 51511
4-1⁄2"	Very Fine (Blue) Medium (Maroon) Coarse (Brown)	51512 51513 51514
5"	Very Fine (Blue) Medium (Maroon) Coarse (Brown)	51515 51516 51517
6"	Very Fine (Blue) Medium (Maroon) Coarse (Brown)	51518 51519 51520
7"	Very Fine (Blue) Medium (Maroon) Coarse (Brown)	51521 51522 51523

Very Fine (Blue)

Coarse (Brown)

Medium (Maroon)

8"

Hook & Loop Style Back-up Pads



1/4 3(6)11					
Max. RPM	Part No.				
16,000	51561				
16,000	51562				
16,000	51563				
13,000	51569				
10,000	51575				
8,000	51577				
6,000	51578				
4,500	51579				
	16,000 16,000 16,000 13,000 10,000 8,000				

Do not exceed the maximum RPM of the back-up pad.

Plastic Button Style Back-up Pads




1/4" Stem							
Dia.	Max. RPM	Part No.					
1-1/2"	30,000	51550					
2" 25,000		51551					
3" 20,000		51552					
4"	12,000	51553					

Brushing Guide Proper Brushing Procedure

For maximum brushing results, use the lightest pressure necessary to accomplish the job. Let the wire tips do the work; excessive pressure can cause wire breakage.






Correct




Incorrect

Wire Brushes vs. Abrasive Wheel

Power brushing removes dirt, contaminants and oxides from base material, not the base material itself. In some applications, hard abrasive wheels will remove the base







Abrasive Wheel

Safety Guide

No. 1 **Safety Goggles**

Safety goggles or full face shields worn over safety glasses with side shields must be worn by all operators and others in the area of power brush operations.

No. 2 **Protective Equipment**

Appropriate protective clothing and equipment must be used where there is a possibility of injury that can be prevented by such clothing or equipment.

No. 3 **Guards**

51524

51525

51526

ndustrial Brushes

Keep all machine guards in place.

No. 4 Speeds

Observe all speed restrictions indicated on brushes, containers, labels or printed pertinent literature. MSFS, "Maximum Safe Free Speed" should not be exceeded under any circumstances.

Bench and Straight Grinder Wire Wheels



Steel Wire Wheels

- Provide fine to medium brushing action.
- Excellent for uneven surfaces.

Diameter	Wire Size	Arbor Hole	Face Width	Max. RPM	Part No.
C	014	E/0" 1/0"	1/2"	C 000	BW-605
6"	.014	5/8"-1/2"	1"	6,000	BW-610



Wire Brushes / Wheels

Knot Style for Small Angle Grinders



Standard Twist Wheels

- · Cleaning grooves and bead welds.
- Easy to handle.

7 H No. 70							
Dia.	Wire	Arbor Hole	Face	Max.	Part No.		
Dia.	Size	AIDUI HUIE	Width	RPM	Steel	Stainless	
		5/8"-11 UNC			BW-750 •	BW-9750 •	
		1/2"-13 UNC			BW-751 •	BW-9751 •	
4"	014	14 M-10 x 1.25	M-10 x 1.25	20.000	BW-752 •	BW-9752 •	
4"	N	M-10 x 1.50	1/2	1/2 20,000	BW-753 •	BW-9753 •	
		M-14 x 2.0			BW-754 •	BW-9754 •	
		3/8"-24 UNF			BW-755 •	BW-9755 •	



Stringer Bead Twist Wheels

- Cleaning of stringer bead welds.
- Great for fillet weld cleaning.



KEY

	ı
1111	ı
	_

14)	Dia.	Wire	Arbor Hole	Face			
	Dia.	Size	Arbur nuie	Width R		Steel	Stainless
	4" .020		5/8"-11 UNC	JNC .25 .50 3/16" 20,000 BW-841 BW-842 BW-843 BW-84	/4.011 00 000	BW-840 •	BW-9840 •
		000	1/2"-13 UNC			BW-841 •	BW-9841 •
			M-10 x 1.25			BW-842 •	BW-9842 •
		.020	M-10 x 1.50		BW-843 •	BW-9843 •	
			M-14 x 2.0			BW-844 •	BW-9844 •
			3/8"-24 UNF			BW-845 •	BW-9845 •

Crimped Wire Wheels for Small Angle Grinders



Crimped Steel Wire Wheels

- Fast cleaning action.
- · Surface preparation.

Dia.	Wire Size	Arbor Hole	Face Width	Max. RPM	Part No.
	.014	5/8"-11 UNC			BW-450 •
		1/2"-13 UNC			BW-451 •
4"		M-10 x 1.25	1/2"	14,000	BW-452 •
4		M-10 x 1.50	1/2	14,000	BW-453 •
		M-14 x 2.0			BW-454 •
		3/8"-24 UNF			BW-455 •

Small Diameter Crimped Wire Wheels



Small Wire Wheels



- Clean internal surfaces and hard-to-reach areas
- For use on high speed grinders.

` -	- 1
	T

9	MODE A.	Wire	Arbor	Face	Max.	Part No.	
	Dia.	Size	Hole	Width	RPM	Steel	Stainless
		.0118				BW-701 –	
		.014				BW-702 –	
		.014				BW-702C •	
		.0118				BW-703 –	
	3"	.014	1/2"-3/8"	1/2"	20,000	BW-704 –	BW-9704 -
		.014				BW-704C •	

Brush Drive Arbor

Brush drive arbors are display packed for P.O.P. merchandising.

Arbor Size: 1/2" Shank Size: 1/4" Overall Length: 1-3/4" Part No. BW-594



Threaded Arbor Adapters

Small, high speed angle grinder adapters used to convert 5/8"-11 UNC.



Arbor Hole	Part No.
5/8"-11 to M-10 x 1.25	BW-590 –
5/8"-11 to M-10 x 1.50	BW-591 –
5/8"-11 to 3/8"-24	BW-592 –

Stem Mounted Wire Brushes



Crimped Wire End Brushes w/ 1/4" Stem



Dia.	Wire	Trim	Max.	Part No.	
Dia.	Size	Length	RPM	Steel	Stainless
	.006				BW-9206 -
	.0104			BW-206 -	
3/4"	.014	7/8"	22,000	BW-204 -	
	.020			BW-203 -	
	.020			BW-203C •	
	.006			BW-210 –	BW-9210 -
1"	.014	7/8"	22,000	BW-209 –	
	.020			BW-215C •	



Knot Style End Brushes w/1/4" Stem

Dia.	Wire	Trim	Max.	Part No.		
Dia.	Size	Length	RPM	Steel	Stainless	
	.014			BW-207 –		
3/4"	.020	7/8"	22,000	BW-208 –		
	.020			BW-208C •		
	.014			BW-211 –		
1-1/8"	.020	7/8"	22,000	BW-212 –		
	.020			BW-212C •	BW-9212C •	

KEY POP a Box - Bulk



Wire Brushes / Wheels

Stem Mounted Wire Brushes

Crimped Wire Brushes w/1/4" Stem













Diameter	Wire Size	Trim Longth	Max. RPM	Part No.	
Diameter	wire Size	Trim Length	IVIAX. KPIVI	Steel	Stainless
Light Duty (Cup Brush				
2-1/2"	.014	1"	4,500	BW-213C •	
Wheels					•
O"	2" .0118	1/2"	20,000	BW-217 -	
	1/2	20,000	BW-217C •		
	.008		20,000	BW-218 -	
3"	.0118	1"		BW-219 -	
ა	.014	_	20,000	BW-220 -	BW-9220 -
	.014			BW-220C •	
Flared Whe	els				
0.1/0"	014	1"	20,000	BW-216 -	
2-1/2	2-1/2" .014		20,000	BW-216C •	
Encapsulate	d Wire Wheel				
3"	.0118	1"	20,000	BW-214C •	

Crimped Wire and Knot Style Cup Brushes



- · Fast cleaning action.
- Rust removal.
- · Surface Preparation.



Dia.	Wire Size	Arbor Hole	Trim Longth	m Length Max. RPM		Part No.		
Dia.	WIIE SIZE	AIDUI HUIC	IIIIII Leilyiii			Stainless		
4"	.014	5/8"-11	1 2/0"	0.000	BW-339 ¤			
4"	.020	0/8 -11	1-3/8"	9,000	BW-340 ¤			
5"	.020	5/8"-11	1-3/8"	9,000	BW-350 ¤	BW-9350 ¤		
6"	.014	E/0" 11	1-1/4"	9 000	BW-359 ¤			
0	.020	5/8"-11	1-1/4	8,000	BW-360 ¤			

Heavy Duty Knot Brushes

- · Fast cleaning action on large surfaces.
- · Cleaning corners and hard-to-reach places.
- · Long lasting.





Dia.	Wire Size	Arbor Hole	Trim	Max. RPM	Row Count	Part No.	
Dia.	Wile Size	AIDUI HUIC	Length	Length Wax. NEW		Steel	Stainless
	.014		1-1/4"		1	BW-440 ¤	
4"	.020	5/8"-11	1-3/8"	9,000	2	BW-2441¤	
	.023		1-1/4"		1	BW-441 a	BW-9441¤
	.014					BW-459 ¤	
	.023		1-1/4"	7,000	1	BW-461 ¤	
6"	.035	5/8"-11				BW-460 ¤	BW-9460¤
	.023]	1-3/8"	6.600	2	BW-2461¤	BW-9461¤
	.035		1-3/0	טטס,ס	۷	BW-2460¤	

Cup Brushes for Small Angle Grinders



- · Removes light rust & oxides.
- · Fast brushing action.





Dia.	Wire Size	Arbor Hole	Trim Lenath	Max. RPM	Part No.	
Dia.	Wife Size	Arbur nuie	IIIIII LEIIYIII	IVIAX. NEIVI	Steel	Stainless
		5/8"-11 UNC			BW-320 •	
	1/2"-13 UNC			BW-321 •		
2-3/4"	0.0/4	M-10 x 1.25	7/8"	14,000	BW-322 •	
2-3/4	.014	M-10 x 1.50			BW-323 •	
		M-14 x 2.0			BW-324 •	
		3/8"-24 UNF			BW-325 •	
3-1/2"	.014	5/8"-11 UNC	3/4"	12,000	BW-326 ¤	BW-9326 ¤

KEYPOPBoxBulk



Wire Brushes / Wheels

Cup Brushes for Small Angle Grinders

Knot Style Brushes

- · Weld cleaning.
- · Pipe bevel cleaning.
- · Cleaning hard-to-reach areas.





Dia. Wire Size	Wire Size	Arbor Hole	Trim	Max. RPM	Row Count	Part No.	
Dia.	WITE SIZE	ALDOL HOLE	Length	IVIAX. NEIVI		Steel	Stainless
		5/8"-11 UNC	13 UNC 0 x 1.25 7/8" 14.000 1		BW-420 •	BW-9420 •	
	0.0/4 04.4	1/2"-13 UNC		14,000	1	BW-421 •	BW-9421 •
2-3/4"		M-10 x 1.25				BW-422 •	BW-9422 •
2-3/4	.014	M-10 x 1.50				BW-423 •	BW-9423 •
		M-14 x 2.0				BW-424 •	BW-9424 •
		3/8"-24 UNF				BW-425 •	BW-9425 •
3-1/2"	.020	5/8"-11 UNC	7/8"	13,000	1	BW-426 ¤	BW-9426 ¤

Knot Style Wire Wheel Brushes

Standard Twist Wheels

- · Fast cleaning action.
- · Weld cleaning.
- Surface preparation.









Dia.	Dia. Wire Size	Arbor Hole Face Width	Max. RPM	Part No.		
Dia.	Wife Size	Arbur nuie	race wiulii	Max. Hr W	Steel	Stainless
3"	.014	1/2"-3/8"	3/8"	25,000	BW-730C •	BW-720C •
	.014				BW-740 –	
4"	.020	1/2"-3/8"	1/2"	20,000	BW-756 –	
	.020				BW-756C •	
6"	.016	5/8"-1/2"	1/2"	9,000	BW-763 -	BW-9765 -

Stringer Bead Twist Wheels

- · Special construction to prevent unwinding of knots.
- · Cleaning stringer bead welds.
- · Quick mount threaded nut.









Dia.	Wire Size Arbor Hole Face Width Max. RPM	Part No.				
ыа.	Wile Size	Albui nuie	race widdii iviax. nrivi		Steel	Stainless
5"	.020	5/8"-11 UNC	2/16"	12 500	BW-855 •	
3	.020	M-14 x 2.0	3/16" 12,500	12,300	BW-856 •	
6"	.020	5/8"-11 UNC	3/16"	12,500	BW-861 •	BW-862 •
0	.023	3/0 -11 UNG	1/2"	9,000	BW-760 •	
6-7/8"	.020	5/8"-11 UNC	3/16""	9,000	BW-865 •	

Packaged Kits

Air Tool / Drill Accessory Kit

Contains 2 brushes and 2 wheels:

- 3/4" crimped wire end brush, .020 steel wire.
- 1-3/4" crimped wire cup brush, .0118 steel wire.
- 3" crimped wire wheel, .014 steel wire.
- 3" abrasive flap wheel, 80 grit/ aluminum oxide grain.

Part No. BW-GK



Mini Grinder Kit

Contains 1 brush and 2 wheels:

- 2-3/4" knot wire cup brush, .014 steel wire.
- 4" stringer bead knot wire wheel, .020 steel wire.
- 4-1/2" abrasive flap disc, 60 grit / zirconium grain.

Part No. BW-DK



Industrial Accessories

Pipe Jacks / Scratch Brushes / Industrial Tape

Folding V-Head Pipe Stand

- 2,000 lb. capacity.
- Handles up to 36" (900 mm) pipe.
- Folding legs.
- Set screw.
- 1-1/2" acme adjustment thread.
- · V-head locks for storage.
- · Lightweight (21 lbs.).
- · Convenient carrying handle.
- · Large comfortable adjustment handle.
- 1" (25 mm.) square legs.
- · Adjustable 27" to 42" height.

Part No. FVJACK



Tall V-Head Stand

- 2.500 lb. capacity
- Handles up to 36" (900 mm) pipe.
- Strut tension plate for lateral support.
- 1" square tube base construction.
- Lockwasher for fast height positioning.
- 1-1/2" (38 mm) Acme threads for accurate safe, setting.
- Heavy Duty, convenient adjustment handle.
- Set screw for doubles your margin of safety.
- Set screw locks head to stand for transportation.
- Load tested for quality assurance.

Part No. HDVJACK

Ball Transfer Head

Fits over V-head.

Part No. OBTH






THE PROPERTY OF THE PARTY OF TH



Scratch Brushes

Weld Cleaning and Inspection Brushes

Choice of brush material is stainless steel or straight brass, both materials are .006 gauge wire.



^{* &}quot;C" items are packed 2 per card.

Curved Handle Brushes

Block Size	Brush	No. of	Trim	Part No.	
DIUCK SIZE	Length Row	Row	Length	Steel	Stainless
13-3/4" x 15/16"	6"	3 x 19	1-1/8"	BW-103	BW-9103
13-3/4" x 1-1/8"	0	4 x 19	1-3/16"	BW-104	BW-9104

Shoe Handle Brush

Block Size	Brush	No. of	Trim	Part No.	
DIUGK SIZE	Length	Row	Length	Steel	Stainless
10" x 1-1/16"	5"	4 x 16	1-3/16"	BW-112	BW-9112

Acid Brushes

Width	Trim Length	Overall Length	Part No.
5-1/16"	3/4"	E 2/4"	BW-180 ¹
3-1/10	3/4	5-3/4"	BW-180C*
1/2"	3/4"	5-3/4"	BW-181 ¹

^{* &}quot;C" items are packed 6 per card.

Chipping Hammer Brushes

Brush material is .012 gauge steel wire.

5 5					
	Block Size	Brush Length	No. of Row	Trim Length	Part No.
	4-5/8" x 7/8"	4-1/2"	3 x 15	1-1/8"	BW-135
					BW-135C*

^{*} Stock numbers ending in "C" are display packed for P.O.P. merchandising.

INDUSTRIAL TAPE

Tartan™ Masking Tape 200

- · Utility-purpose masking tape with rubber adhesive for general use.
- Suited for holding, bundling, sealing, and other non-critical masking applications.
- Use for jobs where pressure sensitive tape is needed.
- · Economical natural colored tape available in three widths.
- Use in temperatures up to 200° F.
- · Natural color tape.

Part No./UPC	Description	
02120071183	1/2" x 36 yds. (12 mm x 33 m)	
02120071180	1" x 36 yds. (25 mm x 33 m)	
02120071177	2" x 36 yds. (50 mm x 33 m)	



Double Coated Urethane Foam Tapes 4016

- This tape has an acrylic adhesive that seals, cushions vibrations, resists impacts, and insulates.
- It adheres to most clean, dry, rough, or smooth
- Resists heat up to 380° F for short periods and 225° F for an extended time.

Part No./UPC	Description		
02120006453	1/2" x 36 yds. (12 mm x 33 m)		
02120006455	1" x 36 vds. (25 mm x 33 m)		



^{**} Hand tied

¹ Sold by the gross.