

## Cable - Shrink Wrap / Power Cord / Cylinder Carts

### Shrink Wrapped Cable Welding Cable 600V

Shrink wrapped welding cable is packaged in a Polyethylene shrink wrap package for 25', 50', and 100' lengths. This convenient, durable, and attractive package ships better than boxed material and saves showroom shelf space and valuable warehousing space. This cable is abrasion resistant and has excellent flexibility and strong color retention.

\*Available in most sizes



### 25' 8/3 ST 0° C to 60° C Power Supply Cord

Constructed with #8 AWG 133/29 bare copper, this 25' power supply cord has black, white, and green (ground) conductors and a matte black Polyvinyl Chloride jacket. The male/cap (end) and female/connector end (receptacle) are NEMA 6-50P and NEMA 6-50R black, PVC, polarized connectors.

- U.L. Type ST, CSA Approved
- 40 Amps, 250 Volts, 1,000 Watts

Part No. 8325



### Copper Conductor AWG Guide



Electrode Distance from Welding Equipment (ft.) *1/2 total circuit length									
Amps	50	75	100	125	150	200	250	300	350
100	4	4	2	2	1	1/0	2/0	3/0	4/0
150	3	3	1	1/0	2/0	3/0	4/0		
200	2	1	1/0	2/0	3/0	4/0			
250	1	1/0	2/0	3/0	4/0				
300	1	2/0	3/0	4/0					
350	1/0	3/0	4/0						
400	2/0	3/0	4/0						
450	3/0	4/0							
500	4/0	4/0							
600	250 MCM								
750	350 MCM								
900	500 MCM								

\* Based on voltage drop of 4 volts per ICEA and NEMA specifications

Standard package information: 250', 500' and single length N/R reels  
minus 10%- plus 20%

Cut and fitted cable assemblies also available. Call for details.



### Light and Medium Duty Cylinder Trucks

These light and medium cylinder trucks are perfect for hobbyists, plumbers, maintenance departments, farmers, garages, and almost any application with hard surface floors.



Part No. CTR-6



Part No. CTR-6-1T



Part No. CTR-8



Part No. CTR-8-1T

Part No.	Cylinder		Wheels		Base Dimension	Height	Width	Depth	Wt. (lbs.)
	Acetylene	Oxygen	No.	Type					
CTR-6	40/60	60/90	100610	Semi-pneumatic	8" x 15.5"	42"	19"	12"	13
CTR-6-1T	40/60	60/90	100610	Semi-pneumatic	8" x 15.5"	42"	19"	12"	18
CTR-8	40/120	122/160	100810	Semi-pneumatic	8" x 19"	44"	23"	13.5"	23
CTR-8-1T	40/120	122/160	100810	Semi-pneumatic	8" x 19"	42"	19"	12"	19
CTRB-10-2T	40/120	122/244	101020	Semi-pneumatic	9.25" x 19.5"	46.5"	25.5"	17"	35

## Small and Medium Cylinder Trucks

Our sturdy "U" frame design gives these models maximum strength and considerable stability. These models come with retaining chains and the CTR 200 series is available in several wheel sizes and configurations.



Part No. CTR-10



Part No. CTR-212-1T



Part No. CTR-214-1T



Part No. CTR-216-1T

Part No.	Cylinder		Wheels		Base Dimension	Height	Width	Depth	Wt. (lbs.)
	Acetylene	Oxygen	No.	Type					
CTR-10	40/120	122/160	101010	Semi-pneumatic	9" x 18"	39"	23.5"	14.5"	30
CTR-212-1T	120	244	101210	Semi-pneumatic	12" x 21"	42"	26.5"	19.5"	38
CTR-214-1T	120	244	101410	Semi-pneumatic	12" x 21"	42"	27"	19.5"	44
CTR-216-1T	120	244	101611	Semi-pneumatic	12" x 21"	42"	28"	22"	48

## Large Cylinder Trucks

The 500 series is a workhorse for larger cylinders. The 600 series is 4" wider to accommodate a 100# propane cylinder.



Part No. CTR-14



Part No. CTR-516-5T



Part No. CTS-520-1T



Part No. CTR-520-1T

Part No.	Cylinder		Wheels		Base Dimension	Height	Width	Depth	Wt. (lbs.)
	Acetylene	Oxygen	No.	Type					
CTR-14	300	244/300	101410	Semi-pneumatic	13" x 24"	43.5"	30"	20"	48
CTRV-514-1T	300	244/300	101410 100351	Semi-pneumatic 3.5" Casters	13" x 24"	37.25"	30"	35"	53
CTR-516-1T	300	244/300	101611	Semi-pneumatic	13" x 24"	44"	31"	22"	52
CTR-516-5T	300	244/300	101650/SC-11	Pneumatic	13" x 24"	44"	36"	21"	52
CTS-520-1T	300	244/300	SC-13	Steel	13" x 24"	44"	34"	23"	56
CTR-520-1T	300	244/300	102010	Semi-pneumatic	13" x 24"	44"	34"	24"	70
CTS-24	300	244/300	102410	Steel	13" x 24"	44"	34"	25.5"	62
CTR-616-1T	100#PROP	244/300	101611	Semi-pneumatic	13" x 28"	44"	37"	21"	55
CTR-616-5T	100#PROP	244/300	101650/SC-11	Pneumatic	13" x 28"	44"	40"	21"	56

## Handtrucks / Cylinder Holders / Cylinder Carts

### Handtruck for Dockman and Cylinder Transport

- May be used to move small boxes and equipment.



Part No. WT-10\*



Part No. CT-12-3

Part No.	Cylinder		Wheels		Base Dimension	Ht.	Width	Depth	Wt. (lbs.)
	Acetylene	Oxygen	No.	Type					
WT-10	300	244/300	101020	Semi-pneumatic	9" x 13.5"	47"	18"	11"	33
CT-12-3	(3) 300	244/300	101222	Pneumatic	9" X 25"	31"	31"	13.5"	53

### Cylinder Holders

- All cylinder holders are packed 1 to a carton.
- 10 cylinder holders to a master carton.



Part No.	Weight	O.D. Cylinder Size
CH-104	2 lbs., 10 oz.	3-7/8" - 4-3/8"
CH-145	2 lbs., 12 oz.	5-1/4" - 5-3/4"
CH-105	3 lbs.	5-3/4" - 6-3/8"
CH-106	3 lbs., 4 oz.	6-1/2" - 7-1/4"
CH-107	3 lbs., 6 oz.	7-1/4" - 8"
CH-108	3 lbs., 8 oz.	8" - 8-3/4"
CH-185	3 lbs., 11 oz.	8-1/2" - 9"
CH-109	3 lbs., 13 oz.	9" - 9-3/4"
CH-110	4 lbs., 4 oz.	10" - 10-3/4"
CH-112	4 lbs, 12 oz.	12" - 13" MAPP®
CH-114	5 lbs., 10 oz.	14-1/2" - 15 1/4"

### Heavy Duty and Industrial Trucks

The CHT Series carts are used for transporting cylinders, boxes, small equipment, etc. These carts have excellent control and maneuverability in warehouse situations. The CHT-10-3 is available with an optional stair climber. The Tandem Series is designed for narrow aisles and doors and works well in door-to-door service.



Part No. CHT-10-3S/C



Part No. CTR-TANDEM-10



Part No.	Cylinder		Wheels		Base Dimension	Height	Width	Depth	Wt. (lbs.)
	Acetylene	Oxygen	No.	Type					
CHT-10-3	300	244/300	101030	Pneumatic	9" x 13.5"	55.5"	22"	11.5"	31
CHT-10-3S/C	300	244/300	101030	Pneumatic	9" x 13.5"	55.5"	22"	11.5"	33
CHT-10-2	300	244/300	101020	Semi-pneumatic	9" x 13.5"	55.5"	22"	11.5"	31
CHT-14-1	300	244/300	101410	Semi-pneumatic	9" x 13.5"	55.5"	19"	15"	33
CTR-TANDEM-10	40/120	60/122	101010	Semi-pneumatic	10.5" x 17.5"	54"	14.5"	19"	26
CTR-1610-2H	300	244/300	101020	Semi-pneumatic	15" x 23"	46"	22"	31.5"	52
CTR-3016-5	300	244/300	101650/SC-11	Pneumatic	13" x 24"	62"	35"	38.5"	72
CTR-3016-5FW	300	244/300	101650/SC-11	Pneumatic	13" x 24"	62"	38"	38.5"	130
NITR-40	7.5"	7.5"	N/A	N/A	N/A	26"	8.5"	9"	6

## Replacement Wheels / Brackets and Stands / MIG Carts

### Replacement Wheels

Part No.	Wheel Size	Bearing	Wheel	HUB	Corresponding Model No.
100610	6" x 1.50" x 1/2"	Ball Bearing	Semi-pneumatic	Steel	CTR-6, CTR-6-1T
100810	8" x 1.75" x 1/2"	Ball Bearing	Semi-pneumatic	Steel	CTR-8, CTR-8-1T
101010	10" x 1.75" x 5/8"	Ball Bearing	Semi-pneumatic	Steel	CTR-10, CTR-TANDEM-10
101020	10" x 2.75" x 5/8"	Ball Bearing	Semi-pneumatic	Steel	CTRB-10-2T, WT-10, CHT-10-2, CTR-1610-2H
101030	10" x 3.50" x 5/8"	Ball Bearing	Pneumatic	Steel	CHT-10-3, CHT-10-35/C
101210	12" x 1.75" x 5/8"	Ball Bearing	Semi-pneumatic	Steel	CTR-212-1T
101222	12" x 3.50" x 3/4"	Ball Bearing	Pneumatic	Steel	CT-12-3
101410	14" x 1.75" x 3/4"	Ball Bearing	Semi-pneumatic	Steel	CTR-214-1T, CTR-14, CTRV-514-1T, CHT-14-1
101611	16" x 1.75" x 1"	Nylon	Semi-pneumatic	Steel	CTR-216-1T, CTR-516-1T, CTR-616-1T
101650/SC-11	16" x 4" x 3/4"	Ball Bearing	Pneumatic	Steel	CTR-516-5T, CTR-616-5T, CTR-3016-5, CTR-3016-5FW
102010	20" x 3.25" x 1"	Nylon	Semi-pneumatic	Steel	CTR-520-1T
102410	24" x 2.5" x 1"	Nylon	Steel	Steel	CTS-24
100351	3" x 1/2"	Ball Bearing	Caster	Steel	CTRV-514-1T
SC-13	20" x 2-1/2"	Nylon	Steel	Steel	CTS-520-1T

### Brackets and Stands



Part No.	Cylinder		Height	Width	Depth	Wt. (lbs.)
	Acetylene	Oxygen				
NITR-40	7.5"	7.5"	26"	8.5"	9"	6

### Mini-MIG Carts

This MC-61 is a bolt-together MIG cart. Everything comes ready to assemble in a compact UPS shippable box. The MC-61 is sturdy yet light weight. The dimensions 17.25" H x 15.75" W x 27" D.

Weight 23 lbs.

- 6" plastic wheels

**Part No. MC-61**



### MIG Carts

Lightweight for transporting a MIG welder and accompanying gas cylinder. 101020 Semi-pneumatic wheels. The cart is 50 lbs. and has dimensions of 42" H x 28" W x 19.5" D and a base dimension of 10" x 10".

**Part No. SP910312**



This cart is designed to carry a variety of mini-MIGs, inverters and plasma machines. The dimensions are 17" H x 14" W x 36" D.

Weight 38 lbs.

- 8" plastic wheels

**Part No. UM-8**



### Cryogenic Carts

Frames braced for years of dependable service. 12" x 2-1/2" CIRB wheels in the front and 6" x 2-1/2" CIRB wheels in the back. The cart is 109 lbs. and has dimensions of 43" x 25".

**Part No. LCT-12-6**



## Soapstone

- All white texture for excellent marking quality.
- Grain cut to ensure good strength and long service life.
- Marks will not contaminate welds and are easily removed.
- Low water content for increased hardness and resistance to breakage.



Part No. NS-16



Part No. NS-16A

Part No.	Description	Packaged
NS-16	Flat	144 pieces/ pk
NS-16A	Round	
NS-16B	Square	



Part No. NS-16B



## 

### DYKEM® TXP®

The TEXPEN® stands out for its distinctive fine, medium and bold oil-based paint markings. Its stainless steel-ball valve action tip writes through oil, grease and underwater without losing legibility or brightness even in extreme weather conditions.



Part No. 16063

#### TEXPEN®

Color	Fine	Medium	Broad
Black	16030	16033	16034
Blue	16010	16013	16014
Green	16040	16043	16044
Orange	16100	16103	16104
Red	16020	16023	16024
White	16080	16083	16084
Yellow	16060	16063	16064

### DYKEM® DALO®

The DALO® Marker is a marking pen with medium and bold tips that holds a high capacity of oil-based paint and is a larger version of the TEXPEN®. Its stainless steel-ball valve action tip writes through oil, grease, and underwater without losing legibility or brightness even in extreme weather conditions.

- Writes sharp, defined, bright marks on any surface including metal, plastic, glass, concrete, rubber & more.
- Ergonomically correct marker that enables you to mark at all angles, even upside down.
- Marker retains its shape.
- Paint flow is controlled by the bulb at the end of the barrel.
- Drying time: 25-35 minutes.



Part No. 26033

#### DALO® Marker

Color	Medium	Broad
Black	26033	26034
Blue	26013	26014
Green	26043	26044
Orange	26103	26104
Red	26023	26024
White	26083	26084
Yellow	26063	26064