

## Hose Reels

### General Industrial Reels

The ReelTek spring driven hose reel is ideal for general industrial applications. Base and guide arm are made of heavy-gauge steel stampings with reinforced ribs to increase structural strength. The composite spool contains the drive spring and reduces the total number of required parts.

- Adjustable guide arm locates to seven positions providing multiple mounting positions.
- Easy to mount slotted mounting holes for safer and easier installation.
- Oversized main shaft increases support.


**RT6500LP**

Part No. (w/ hose)	Hose Length	PSI	Hose I.D.	Hose O.D.	(M)NPTF Outlet	(F)NPTF Inlet	Dimensions			Weight (lbs.)
							Height	Length	Width	
RT4500LP	50'	300	1/4"	.500"	1/4	3/8	17.875"	16.5"	5.75"	25
RT6350LP	35'	300	3/8"	.640"	1/4	3/8	17.875"	16.5"	5.75"	23
RT6500LP	50'	300	3/8"	.640"	1/4	1/2	17.875"	16.5"	6.25"	29
RT8500LP	50'	300	1/2"	.781"	1/2	1/2	17.875"	16.5"	6.25"	35

### Premium Industrial Reels

Reelcraft's spring driven series 4000 and 5000 reels are all steel construction and compact for a wide range of applications with critical space requirements. The Quiet Speed latch mechanism offers quiet operation combined with latch cam technology insuring longer latching life and trouble-free performance.

- Corrosion resistant powder coated paint for long service life.
- Easily mounts on wall, floor, ceiling or truck.
- Permanently lubricated bearings and swivels extend service life.


**46250LP**

Part No. (w/ hose)	Hose Length	PSI	Hose I.D.	Hose O.D.	(M)NPTF Outlet	(F)NPTF Inlet	Dimensions			Weight (lbs.)
							Height	Length	Width	
<b>Low Pressure Air / Water Reels</b>										
44200LP	20'	300	1/4"	.500"	1/4	3/8	12.875"	12.625"	5.375"	17
44350LP	35'	300	1/4"	.500"	1/4	3/8	12.875"	12.625"	5.375"	20
54500LP	50'	300	1/4"	.500"	1/4	3/8	14.5"	13.5"	6"	26
46250LP	25'	300	3/8"	.640"	1/4	3/8	12.875"	12.625"	5.375"	22
56350LP	35'	300	3/8"	.640"	1/4	3/8	14.5"	13.5"	6"	25
56500LP	50'	300	3/8"	.640"	1/4	3/8	14.5"	13.5"	6"	36
A58250LP	25'	300	1/2"	.781"	3/8	3/8	17.5"	16.5"	6"	29
A58500LP	50'	300	1/2"	.781"	1/2	3/8	17.5"	16.5"	6"	44
<b>Medium Pressure Oil Reels</b>										
56300MP	30'	2250	3/8"	.780"	3/8	3/8	14.5"	13.5"	6"	30
<b>High Pressure Grease Reels</b>										
54300HP	30'	5000	1/4"	.590"	1/4	1/4	14.5"	13.5"	17.5"	30


**A58500LP**

### Heavy Duty Industrial Reels

Reelcraft's spring driven series 7000 and 80000 reels are very robust and ideal for the most demanding applications. These reels incorporate all steel construction and a baked-on powder coat finish to produce a rugged corrosion resistant product suitable for a wide variety of heavy duty applications.

- Guide arm is field adjustable for wall, ceiling or truck mounting positions.
- Engineered forms and ribs provide superior support.

Part No. (w/ hose)	Hose Length	PSI	Hose I.D.	Hose O.D.	(M)NPTF Outlet	(F)NPTF Inlet	Dimensions			Weight (lbs.)
							Height	Length	Width	
<b>Low Pressure Air / Water Reels</b>										
76000LP*	70'	500	3/8"	.688"	N/A	1/2	20.25"	19"	7"	42
76500LP	50'	300	3/8"	.688"	1/4	1/2	20.25"	19"	7"	47
76700LP	70'	300	3/8"	.688"	1/4	1/2	20.25"	19"	7"	50
78500LP	50'	300	1/2"	.844"	3/8	1/2	20.25"	19"	7"	51
F79250LP§	25'	50	3/4"	1.188"	3/4	3/4	20.25"	19"	7"	53
811000LP	100'	300	3/8"	.688"	3/8	1/2	25.375"	24"	11.375"	92
821000LP	100'	300	1/2"	.845"	1/2	1/2	25.375"	24"	11.375"	101
830500LP	50'	250	3/4"	1.188"	3/4	3/4	25.375"	24"	11.375"	88
D830750LP	75'	250	3/4"	1.188"	3/4	3/4	25.375"	24"	11.375"	112
<b>Medium Pressure Oil Reels</b>										
820000MP*	75'	1500	1/2"	.815"	N/A	1/2	25.375"	24"	11.375"	79


**78500LP**

§ Supplied with fuel grade hose. \*Hose not included.

## Power and Light Cord Reels

Reelcraft's spring driven power and light cord reels offer many different styles of outlets and lamps. Easy to mount and structurally strong, the power cord and light reels have a robotically welded heavy gauge steel frame that attaches to most structurally sound surfaces. Multiple guide arm positions allows for versatile uses and easier field adjustment. The drive mechanism is enclosed for protection against the environment. Fewer components increase the service life of the reel and improve performance.

- All models UL listed at 115 volt 60 HZ single phase; reels without cord suitable for 220 volt
- Incandescent bulb 75 watt maximum.
- For indoor non-weather tight applications only.

Part No. (w/ cord)	Accessory	Cord Specifications			Volts	AMPS	Weight (lbs.)
		AWG	# Cond.	Length			
L40501622	Fluorescent	16	2	50'	115	0.3	24
L40501631	Incandescent	16	3	50'	115	13	22
L45451233	Single receptacle	12	3	45'	115	15	28
L45451237	Duplex outlet box w/GFCI(F)	12	3	45'	115	20	29
L55501233	Single receptacle	12	3	50'	115	15	47
L55501237	Duplex outlet box w/GFCI(F)	12	3	50'	115	20	47



## Spring Driven Composite Reels

Reelcraft's S series reels are made of corrosion proof, tough polypropylene, which extensive tests have shown to be highly resistant to the majority of acids and alkalis. This design both protects the hose and allows easy cleaning of both hose and reel.

- Economical, durable and lightweight.
- Standard pivot bracket so the reel can swing from side to side.
- Corrosion resistant and durable outer case is UV stabilized and impact resistant.

Part No. (w/ hose)	Hose Length	PSI	Hose I.D.	Hose O.D.	(M)NPTF Outlet	(F)NPTF Inlet	Dimensions			Weight (lbs.)
							Height	Length	Width	
<b>Air &amp; Water Reels: Working temperature 150° F (65° C).</b>										
SGA36500LP	50'	232	3/8"	.621"	3/8	3/8	19"	22.75"	9.5"	23
SGA36650LP	66'	232	3/8"	.621"	3/8	3/8	19"	22.75"	9.5"	27
SGA38500LP	50'	232	1/2"	.781"	1/2	1/2	19"	22.75"	9.5"	27
<b>Water Reel: Garden-style hose end. Working temperature 150° F (65° C).</b>										
SWA38500LP	50'	145	1/2"	.750"	3/4 NH	1/2	19"	22.75"	9.5"	27
<b>Hot Water Wash Reel: Working temperature 185° F (85° C). Working pressure is related to working temperature.</b>										
SHA38500LP	50'	232	1/2"	.781"	1/2	1/2	19"	22.75"	9.5"	27
<b>Chemical Delivery Reel</b>										
SCA38500LP	50'	232	1/2"	.781"	1/2	1/2	19"	22.75"	9.5"	27
<b>Oxygen/Acetylene Reels: Working temperature 150° F (65° C).</b>										
STW34500LP	50'	300	1/4"	.530"	9/8"18(F)LH-RH	9/8"18(F)LH-RH	19"	22.75"	9.5"	27



## Hand Crank Reels

Reelcraft's series 30000 reels feature vibration-proof, self-locking fasteners to ensure assembly integrity. These reels are designed for rugged, heavy duty applications requiring long lengths of hose and large storage capacity. The series H is an economical reel designed for medium duty applications requiring long lengths of hose.

- All bolted construction, no welds.
- Corrosion resistant powder coated paint.

Part No. (w/o hose)	Hose Capacity	PSI	Hose I.D.	Hose O.D.	(F)NPTF Inlet	Dimensions			Weight (lbs.)
						Height	Length	Width	
CA32112L	200'	1000	1/2"	.845"	1/2	20.25"	17.75"	25"	49
CA33112L	100'	1000	1"	1.188"	3/4	20.25"	17.75"	25"	42
CA37118L	100'	300	3/4"	1.380"	1	20.25"	17.75"	34"	58
H19000	100'	1000	3/4"	1.118"	3/4	14"	20"	18.25"	33
H29000	150'	1000	3/4"	1.118"	3/4	19"	20"	24.25"	41



## Hose Reels

### Spring Driven Gas Welding Reels

Reelcraft's spring driven oxygen/acetylene reels have "R" grade hose and seals and can be used with oxygen/acetylene. Oxygen line and gas line have separate input connections for added safety. Twin line hoses meet R.M.A. and C.G.A. Type V.D. grade R specifications for flame resistance and burst strength. "T" grade reels are used for Mapp, propane, natural and other fuel gases plus oxygen/acetylene.

- Designed to increase safety in the work area with a resulting increase in productivity and efficiency.
- Full flow shaft swivels.
- Double-sealed, "O" rings prevent leakage.

Part No. (w/ hose)	Hose Length	PSI	Hose I.D.	Hose O.D.	Dimensions			Weight (lbs.)
					Height	Length	Width	
<b>Oxygen/Acetylene Reels</b>								
TW5400LP*	25'	200	1/4"	.530"	14.5"	13.75"	6"	20
TW5425LP	25'	200	1/4"	.530"	14.5"	13.75"	6"	26
STW3450LP	50'	300	1/4"	.530"	19"	22.75"	9.5"	27
TW7400LP*	60'	200	1/4"	.530"	20.25"	19"	7"	43
TW7450LP	50'	200	1/4"	.530"	20.25"	19"	7"	53
TW7460LP	60'	200	1/4"	.530"	20.25"	19"	7"	55
BA36106L*§	125'	200	1/4"	.530"	20.625"	17.75"	16.625"	50
BA36112L*§	250'	200	1/4"	.530"	20.625"	17.75"	22.625"	57
BA36112LT*§	250'	200	1/4"	.530"	20.625"	17.75"	22.625"	57
<b>Welding Gas (T-Grade) Reels</b>								
TW5400LPT*	25'	200	1/4"	.530"	14.5"	13.75"	6"	20
TW5425LPT	50'	200	1/4"	.530"	14.5"	13.75"	6"	26
TW7400LPT*	60'	200	1/4"	.530"	20.25"	19"	7"	43
TW7450LPT	50'	200	1/4"	.530"	20.25"	19"	7"	54
TW7460LPT	60'	200	1/4"	.530"	20.25"	19"	7"	56
TW84000LPT*	100'	200	1/4"	.530"	25.375"	24"	13"	80
TW84100LPT	100'	200	1/4"	.530"	25.375"	24"	13"	105
TW86000LPT*	75'	200	1/4"	.530"	25.375"	24"	13"	86
TW86075LPT	75'	200	3/8"	.625"	25.375"	24"	13"	99

\*Hose not included. §Hand crank reels.

Acetylene and fuel gas (red) inlet 1/4" FPT / oxygen (green) inlet 1/4" FPT. TW84000 and TW86000 have B size 9/16" - 18UNF male welding inlets.

Part No.	For Reel Series	Hose I.D.	Length	(M)NPTF (fittings)	PSI	Weight (lbs.)
S601031-2	TW5000T / TW7000T	1/4"	2"	female both ends	200	0.70



STW3450LP



TW84100LPT



TW5425LP



S601031-2

### Cable Welding Reels

Reelcraft's series CEA and WC are designed to increase safety in the work area with a resulting increase in efficiency and productivity. Welding cable reels store work lead or electrode lead, up to #2/0, safely and effectively when not in use. They have a continuous current path through a live 400 AMP, 90VDC (maximum) rated enclosed slip ring.

- Designed to increase safety in the work area with a resulting increase in productivity and efficiency.

Part No. (w/o cable)	Reel Capacity				Dimensions			Weight (lbs.)
	#2	#1	#1/0	#2/0	Height	Length	Width	
<b>Hand Crank Oxygen/Acetylene Reels</b>								
CEA30006 §	300'	250'	200'	150'	20.25"	19.375"	21"	49
CEA30012 §	500'	500'	400'	300'	20.25"	19.375"	27"	56
<b>Spring Driven Oxygen/Acetylene Reels</b>								
WC7000	-	50'	50'	50'	20.25"	19"	14.75"	49
WC80001	-	75'	75'	75'	25.375"	24"	16"	80
WC80002	-	100'	-	-	25.375"	24"	16"	81



CEA30006

## Safe-T-Reels

Reelcraft's hand crank Safe-T-Reel Series is ideal for applications where space, weight and flexibility are key, these reels are designed for manual winding of air/water/fuel gases hose, electric cord and welding cable. Versatile in function, select configurations to suit specific needs. Safe-T-Reels offer trouble-free management of large capacities of hose or cord.

Ideal for demanding mobile or stationary applications.

- High rigidity due to one inch shaft with tapered roller bearings.
- Lightweight construction to reduce unnecessary loading.
- Flexible configurations: dual reels offer many combination options.
- Improved performance with high flow swivels.

Model # (w/o cable)	Reel Capacity	AMP	Dimensions			Weight (lbs.)
			Height	Length	Width	
<b>Single Welding Cable: 600 V</b>						
T14600	200'	300	19"	18"	16.25"	22
<b>Dual Side-By-Side Welding Cable (2): 600 V</b>						
T24620	200'	300	19"	18"	29"	50
<b>Dual Stacked Welding Cable (2): 600 V</b>						
T24640	200'	300	38"	18"	16.25"	59



T24620



T24640

Part No (w/o hose)	Hose Length	PSI	Hose I.D.	Hose O.D.	Dimensions			Weight (lbs.)
					Height	Length	Width	
<b>Single Spool Air/Water Reel: Hose not included.</b>								
T111508	150'	300	1/2"	.844"	19"	18"	15.75"	17.5
<b>Single Oxygen/Acetylene T-Grade Reels: Hose not included.</b>								
T122504	150'	200	1/4"	.530"	19"	18"	16.125"	19
	100'	200	1/4"	.530"	19"	18"	16.125"	44
T122606	100'	200	3/8"	.625"	19"	18"	16.125"	19

\* Includes 1/4" x 100' T-Grade twin hose.

## Adjustable Bumper Stops

Part No.	For Reel Series	Hose I.D.	Hose O.D.	Dimensions		Weight (lbs.)
				Diameter	Width	
600521	TH80000 / TW80000 / TH7000	3/8" twin	.680" twin	3.5"	2"	0.45
1HR1004-3	7000 / 80000 / RT800 / RT800 / 5000 / D80000	3/8"	.625" - .749"	3"	1.25"	0.24
2HR1004-3	5000 / A5005 / 7000 / 80000 / RT800	1/2" or 3/8"	.750" - .1.05"	3"	1.25"	0.23
8HR1004-3	TW5000 / TW7000 / TW80000 / TWD80000	1/4" twin	.530" twin	3"	1.25"	0.24



2HR1004-3

600521

## Wall-Mounted Swing Bracket & 340° Pivot Base

Reelcraft's wall-mounted swing bracket (#600626) will pivot approximately 180° (#600980 approximately 140°). All-steel construction with a durable, baked-on powder coat finish.

Reelcraft's 340° pivot base aligns the reel to the direction of hose or cord run. May be mounted upright or hanging.

Part No.	Description	For Reel Series	Weight (lbs.)
600608	340° pivot base	RT / 4000 / 5000 / 5005 / 7000	10
600801	340° pivot base	80000 / D80000 / 30006	10
600801-12	340° pivot base	30012	10
600980	Wall-mounted swing bracket	80000 / D80000	6
600626	Wall-mounted swing bracket	RT / 4000 / 5000 / 5005 / 7000	6



600626



600608