

Chain & Chain Accessories / Plugs and Receptacles

Campbell

Proof Coil Chain/ Grade 30



Part No. 0120422



High Test/ Grade 40



Part No. 0180412

Transport/ Grade 70



Part No. 0510612

Part No.	Working Load Limit (lbs)	Size	Grade	Description	Packaged
0120422	1300	1/4"	30	Proof coil chain	800' drum plated
0120622	2650	3/8"	30	Proof coil chain	550' drum plated
0180412	2600	1/4"	40	System 4	800' drum self color
0180612	5400	3/8"	40	System 4	400' drum self color
0510612	6600	3/8"	70	System 7	400' drum yellow

Load Binders



Part No. 6203604



Part No. 6207803

Part No.	Description	Size
6203604	Double swivel, imported	5/16" - 3/8"
6207504	Ratchet, imported	5/16" - 3/8"
6207803	Ratchet, imported	3/8" - 1/2"

Anchor Shackles

Drop Forged, Self-Colored



Part No. 5410605

Part No.	Size	Working Load Limit (tons)
5410405	1/4"	1/2
5410505	5/16"	3/4
5410605	3/8"	1
5410705	7/16"	1-1/2
5410805	1/2"	2
5411005	5/8"	3-1/4
5411205	3/4"	4-3/4
5411405	7/8"	6-1/2
5411605	1"	8-1/2
5412005	1-1/4"	12

Clevis Grab Hooks



Part No. 4503315

Part No.	Description	Size	Working Load Limit (lbs)
4500404	Carbon steel	1/4"	2600
4500504	Carbon steel	5/16"	3900
4500604	Carbon steel	3/8"	5400
4500804	Carbon steel	1/2"	9200
4503315	Alloy steel	1/4"	4100
4503415	Alloy steel	5/16"	5100
4503515	Alloy steel	3/8"	7100
4503715	Alloy steel	1/2"	12000

SAC Plate Clamp



Part No. 6421000

Part No.	Size	Working Load Limit (tons)
6421000	0 - 1"	1
6421001	0 - 2"	3
6421002	0 - 3"	6

EAGLE Plugs and Receptacles

Power Plugs

- Meets all UL 498 requirements.
- Furnished with blades for 30 and 59 amp configurations.
- Terminals have pressure plates to protect wires.
- Made in U.S.A.



Part No. 0080

Part No.	Description	Rating	Std/Ctn
0021	Plug S21-SP	NMEA14-30 125/250V	1/10
0042	Angle Universal Vinyl 2 Pole, 3 Wire Grounding	50 A/250 V	1/10
0080	Angle Universal Vinyl 3 Pole, 3 Wire Non-Grounding	50-125/250V	1/12

Receptacles

- Meets all UL 498 requirements.
- Heavy gauge steel mounting strap zinc-plated for corrosion resistance.
- For use with copper or aluminum wire, 75° C rated terminals.
- Surface receptacles have patented lay-in terminals and accept up to #4 wire.
- Surface receptacles 3/4" and 1" concentric knockouts and adjustable cord.
- Clamp allows for wiring from bottom or back.
- Made in the U.S.A.



Part No. 1252

Part No.	Description	Rating	Std/Ctn
112BK	3 Pole, 3 Wire Receptacle	50 A-125/250 V	1/10
1252	2 Pole, 3 Wire Receptacle	50 A/250 V	1/10