

**Sanders / Grinders / Cut Off Machines****Die Grinder**

- Ball and needle bearing construction provides smooth power transmission and extended tool life.
- Compact design – slim tool housing comfortably fits in the hand.
- 4" spindle length designed for interior die grinding.
- 35 mm flange diameter.



Specifications	1215
Collet Capacity	1/8" - 1/4"
Rating	120V AC
Switch Type	Lock-On
AMP	4.6
No Load RPM's	27,000
Mounted Point	up to 1"
Polishing Wheel	up to 2"
Length	13"

**4.5" Angle Grinder**

- Multiple uses: grinds, sands, sharpens.
- 2-position assist handle for comfort and control.
- Spindle lock for fast, easy wheel changes.

**Part No. 9290-01**

Specifications	9290-01
Wheel Size and Classifications	4.5" Angle Grinder
Rating	120V AC
AMP	6
No Load RPM's	11,500

**4.5" Angle Grinder w/ Rear Handle**

- Multiple uses: grinds, sands, sharpens.
- Rear handle design for better control for heavy duty applications.
- Dual power switches for barrel or rear handle operation.
- Heavy duty metal gear housing for added durability.
- Quick release guard for versatility.
- Spindle lock for fast, easy wheel changes.

**Part No. 9330-01**

Specifications	9330-01
Wheel Size and Classifications	4.5" Angle Grinder
Rating	120V AC
AMP	6.5
No Load RPM's	11,000

**12"-14" Cut Off Machines**

- Wheel rotation carries sparks, dust and debris away from the operator.
- Reinforced armature windings protects motor against dust and debris.
- Service Minder™ brushes stop the tool when preventative maintenance is required.
- Wrap around side handle mounts left or right.
- Large footplate improves stability and allows greater depth of cut.
- Tool comes set up in fire forward position, and is easily changed to fire reverse.

**Part No. 1364**

Specifications	1364	1365
Wheel Diameter	12"	14"
No Load RPM	5,000	4,300
Depth of Cut	3-7/8"	4-7/8"
Max. Motor HP	4.7	4.7
AMP	15.0	15.0
Rating	120V AC/DC	120V AC/DC
Spindle Thread	5/8" - 11	5/8" - 11

**14" Chop Saw**

- Superior power for fast, efficient cuts.
- Extra motor over-load protection.
- Locking vise with quick release holds awkward material stable for fast and efficient cutting
- Adjustable fence adjusts for bevel cuts ranging from 0-45°. Adjustable depth stop.
- Precision helical steel gears.
- Quality engineering and construction ensures longer life.
- Hold down chain to secure for easy transport.
- Large carrying handle.



Specifications	3814
Wheel Diameter	14"
No Load RPM	3,900
Depth of Cut	6"
Max. Motor HP	4.0
AMP	15.0
Rating	120V AC
Spindle Thread	5/8" - 11